For Class I, II,III,IV Vehicular Gate Operators

Warranty Up to 5 years on commercial installations see website for more info

We stand behind our products



Dimensions: L: 16.5" x W: 18.5" x H: 26" Shipping Weight: 183 LBS

RAM 5700 DC

DC High-Traffic Slide Gate Operator Commercial/Industrial

Mechanics XX



- Brushless DC Motor: 24 VDC, 25 AMPS
- Gearbox: Commercial Synthetic Oil-Bath gearbox to promote smooth and quiet operation. Size 70, Ratio 30:1

Power



- 115 VAC: Single-Phase
- Or 230 VAC (upon request)
- Accessory Power: 24VDC

Design



"Built to Last"

- Chassis: 1/4" Steel, gold zinc plated to inhibit corrosion.
- Cover: High-impact resistant charcoal gray polyethylene plastic. Blends seamlessly with any property

Specs







Gate Travel Speed

Variable Cycle Speed 12"/10"/8"/6" Per Second

Product Highlight RAM 5700 DC

Advanced Battery Back Up System

When the battery has reached 90% of its Battery life, it will then switch to Ultra Low Battery Mode. The system will then stop all gate operations preventing the battery from over- discharge damage.

Through a dip switch the gate can be set to Fail Safe or Fail Secure.

Chain Release

Ability to open gate manually in the event of an emergency.

Mechanical Limit System

Adjust limit switches quickly and accurately with our mechanical system. This helps maintain accurate gate position throughout gate travel.

New Double Board System





LOGIC BOARD

All Ramset DC models use the same two boards

FEATURES

Soft Start Slow Stop

Choose from 4 levels

Left/ Right Switch

 Makes it easy to change the direction of the installation.

One Pass

 Allows for gate to close immediately upon entrance.

Close Delay

4 adjustment to close delay

EP Learn

• Set up photo eyes with the push of a button

Slow Learn Mode

 Allows for a simple slow start/ soft stop set up.
 Measures the lengths of travel from open to close

Battery Back Up System

- Ultra Low Battery Mode saves 10% of your battery for emergencies.
- Includes (2) 12V, 7 Ah
 Batteries

Fail Safe/ Fail Secure

 Should the operator and BBS fail; you now have the option to set up the gate to fail in the open position or to keep it shut.

Training seminars and Webinars available for Technicians and Distributors

- **Easy** installation
- Friendly Tech Support

Reliable

Made in the U.S.A.

Durable

ETL listed. Conforms to UL 325 safety standards